

Page 1/10

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

 Product identij 	fier		
· Relevant ident		1P55315 Part A (Resin) tance or mixture. Adhesive tixture Adhesives	
• Manufacturer , Adhesive Syste A Division of F 9411 Corsair I Frankfort, Illin	ms, Inc. Royal Adhesives & Sea Road		
		ent protection department.	
	ephone number:	and Canada: 1-800-424-9300.	
		27-3887 (collect calls accepted)	
2 Hazard(s) ia	lentification		
· Classification	of the substance or m	ixture	
GHS	502 Flame		
Flam. Liq. 2	H225 Highly flamma	ble liquid and vapor.	
GHS	508 Health hazard		
Muta. 2	H341 Suspected of co	ausing genetic defects.	
	S05 Corrosion		
🐨 🐑 GHS	11214 Caugas annone		
\sim		skin burns and ove damage	
Skin Corr. 1A		skin burns and eye damage. Seve damage	
Skin Corr. 1A	H314 Causes severe H318 Causes serious		
Skin Corr. 1A	H318 Causes serious		
Skin Corr. 1A Eye Dam. 1	H318 Causes serious		

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)



(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture

Hazardous components:80-62-6methyl methacrylate25-50%79-41-4methacrylic acid2.5-10%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Overexposure, remove to fresh air and seek medical attention.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

USA

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling
- Open and handle receptacle with care.
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- Keep receptacle tightly sealed.
- Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

- *REL* Long-term value: 410 mg/m³, 100 ppm
- TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN

79-41-4 methacrylic acid

REL Long-term value: 70 mg/m³, 20 ppm Skin

TLV Long-term value: 70 mg/m³, 20 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment (see listings below)
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eves and skin.

• Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

(Contd. on page 5)

USA

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves
- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Face protection (face shield) • **Body protection:** Protective work clothing Emergency showers and eye wash stations should be available.

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: **Off White** · Odor: *Characteristic* · Odor threshold: Not determined. • *pH-value at 20* •*C* (68 •*F*): 3.3 · Change in condition Melting point: Undetermined. **Boiling point:** 101 °C (214 °F) · Flash point: 10 °C (50 °F) · Flammability (solid, gaseous): Not applicable. 430 °C (806 °F) · Ignition temperature: Not determined. · Decomposition temperature: • Auto igniting: Not determined. · Danger of explosion: Not determined. · Flammable limits: Lower: 2.1 Vol % 12.5 Vol % Upper: · Vapor pressure at 20 $\bullet C$ (68 $\bullet F$): 28 mm Hg • Specific gravity at 20 $\bullet C$ (68 $\bullet F$): 1 g/cm³ (8.345 lbs/gal)

(Contd. on page 6)

USA

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

		(Contd. of page
· Relative density	Not determined.	
· Vapor density	>1 at 20C	
· Evaporation rate	3	
· Solubility in / Miscibility with		
Water:	Insoluble	
· Partition coefficient (n-octanol/w	pater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	Not available	
• Other information	<20 grams/liter [mixed]	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Heat, flames, sparks. Avoid high temperatures. Avoid freezing. Avoid oxygen free atmospheres or inert blanketing.
 Incompatible materials: Reacts with acids. Reacts with oxidizing agents. Reacts with alkalis (bases)

Halogens

Avoid contact with copper, brass and black iron.

• Hazardous decomposition products: Carbon monoxide Carbon dioxide

11 Toxicological information

· Information on toxicological effects

- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7872 *mg/kg* (*rat*)

79-41-4 methacrylic acid

Oral LD50 1332 mg/kg (mouse)

Dermal LD50 500 mg/kg (rabbit)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Strong irritant with the danger of severe eye injury.

(Contd. on page 7)

USA

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation: Must be specially treated adhering to official regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN1133	
· UN proper shipping name		
$\cdot DOT$	Adhesives	
· IMDG, IATA	ADHESIVES	

(Contd. of page 6)

3

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

	(Contd. of page
· Transport hazard class(es)	
·DOT	
F AMMERE FOLD	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
• EMS Number:	F-E,S-D
· Stowage Category	В
· Transport in bulk according to Ann	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Limited Quantities are allowed. Refer to 49 CFR for conditions that apply.
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

USA

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

Chemicals known to cause reproductive toxicity for males:	(Contd. of page
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
(DSL) Canada Dosmestic Substance List All components of this product are on the DSL(Canada Domestic Substance list) or an requirements.	re exempt from DSL
New Jersey Right-to-Know List:	
80-62-6 methyl methacrylate	
79-41-4 methacrylic acid	
New Jersey Special Hazardous Substance List:	
80-62-6 methyl methacrylate	F3, R2
79-41-4 methacrylic acid	CO, F2, R
Pennsylvania Right-to-Know List:	
80-62-6 methyl methacrylate	
79-41-4 methacrylic acid	
Pennsylvania Special Hazardous Substance List:	
80-62-6 methyl methacrylate	i
Cancerogenity categories	· · · · · · · · · · · · · · · · · · ·
EPA (Environmental Protection Agency)	
80-62-6 methyl methacrylate	<i>E</i> , <i>N</i> .
TLV (Threshold Limit Value established by ACGIH)	· · ·
80-62-6 methyl methacrylate	A
MAK (German Maximum Workplace Concentration)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· Department issuing SDS: Environment protection department.

· Creation Date: 11/14/2016

· Date of preparation / last revision 11/17/2016 / -

• Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/14/2016

Trade name: MP55300/MP55305/MP55315 Part A (Resin)

	(Contd. of page 9)	
ACGIH: American Conference of Governmental Industrial Hygienists		
EINECS: European Inventory of Existing Commercial Chemical Substances		
ELINCS: European List of Notified Chemical Substances		
CAS: Chemical Abstracts Service (division of the American Chemical Society)		
NFPA: National Fire Protection Association (USA)		
HMIS: Hazardous Materials Identification System (USA)		
LC50: Lethal concentration, 50 percent		
LD50: Lethal dose, 50 percent		
PBT: Persistent, Bioaccumulative and Toxic		
vPvB: very Persistent and very Bioaccumulative		
NIOSH: National Institute for Occupational Safety		
OSHA: Occupational Safety & Health		
TLV: Threshold Limit Value		
PEL: Permissible Exposure Limit		
REL: Recommended Exposure Limit		
Flam. Liq. 2: Flammable liquids – Category 2		
Skin Corr. 1A: Skin corrosion/irritation – Category 1A		
Eye Dam. 1: Serious eye damage/eye irritation – Category 1		
Skin Sens. 1: Skin sensitisation – Category 1		
Muta. 2: Germ cell mutagenicity – Category 2		
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3		
	USA -	



Page 1/10

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

1 Identification · Product identifier · Trade name: MP55300, MP55305, MP55315 Part B (Activator) · Relevant identified uses of the substance or mixture. Activator · Application of the substance / the mixture Activator · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Adhesive Systems, Inc. A Division of Royal Adhesives & Sealants, LLC 9411 Corsair Road Frankfort, Illinois 60423 Phone Number: 800-552-0299 · Information department: Environment protection department. · Emergency telephone number: ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted) 2 Hazard(s) identification · Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Signal word Danger
Hazard statements
Highly flammable liquid and vapor. Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

(Contd. on page 2)

USA

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

	(Contd. of page
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wear protective gloves / eye protection / face protection.	
Ground/bond container and receiving equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Specific treatment (see on this label).	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a POISON CENTER/doctor if you feel unwell.	
Wash contaminated clothing before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Take off contaminated clothing and wash it before reuse.	
Store locked up.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>s</i> .
Classification system:	
NFPA ratings (scale 0 - 4)	
$\frac{3}{100} Health = 2$	
Fire = 3	
2 Reactivity = 2	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 $Fire = 3$	
PHYSICAL HAZARD 2 Physical Hazard = 2	
Other has and	
Other hazards Possilis of PBT and vPvP assessment	
Results of PBT and vPvB assessment PBT: Not applicable.	
vPvB: Not applicable.	
Composition/information on ingredients	
Chemical characterization: Mixtures	
Description: Mixture	
Hazardous components:	

80-62-6 methyl methacrylate

50-100%

4 First-aid measures

· Description of first aid measures

• After inhalation:

*

*

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3) USA

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam. Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- · Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Open and handle receptacle with care. Ensure good ventilation/exhaustion at the workplace.

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

(Contd. of page 3)

Prevent formation of aerosols.
Information about protection against explosions and fires: Keep container closed when not in use.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

• Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions:
- Protect product from freezing. Protect from heat and direct sunlight.
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

• *Specific end use*(*s*) *No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- Avoia contact with the eyes and ski
- · Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing Date 02/02/2017

Revision Number 1


Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Face protection (face shield) Safety glasses with side shields.



· Body protection:

Emergency showers and eye wash stations should be available. Protective work clothing

9 Physical and chemical properties

· Information on basic physical and c	hemical properties
· General Information	
· Appearance:	
Form:	Paste
Color:	Not determined.
• Odor:	Characteristic
• Odor threshold:	Not determined.
· pH-value:	5
· Change in condition	
Melting point:	Undetermined.
Boiling point:	101 °C (214 °F)
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Flammable limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35 mm Hg)
• Specific gravity at 20 °C (68 °F):	0.96 g/cm ³ (8.011 lbs/gal)
· Relative density	Not determined.
· Vapor density	3.5
· Evaporation rate	3
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
	(Contd. on page 6)

(Contd. of page 4)

USA

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	Not available	
• Other information	<20 grams/liter [mixed]	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- Conditions to avoid Avoid high temperatures. Avoid freezing. Heat, flames, sparks. Direct sunlight
 Incompatible materials:

Reacts with acids. Reacts with oxidizing agents. Reacts with alkalis (bases) Copper and copper alloys.

• Hazardous decomposition products: Carbon monoxide Carbon dioxide Nitrogen oxides Hydrocarbons

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7872 *mg/kg* (*rat*)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye:
- May irritate the eye.

Vapors may be irritating to the eyes.

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)

USA

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

(Contd. of page 6)

3

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

• *NTP* (*National Toxicology Program*) None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.


13 Disposal considerations

· Waste treatment methods

· Recommendation: Must be specially treated adhering to official regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.



Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

	(Contd. of page
· Label	3
· IMDG, IATA	
*	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	В
· Transport in bulk according to Annex	· II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Limited Quantities are allowed. Refer to 49 CFR for conditions that apply.
· UN ''Model Regulation'':	UN 1133 ADHESIVES MIXTURE, 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

 \cdot Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

• TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

(Contd. on page 9)

USA

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

	(Contd. of page 8
· New Jersey Right-to-Know List:	
80-62-6 methyl methacrylate	
· New Jersey Special Hazardous Substance List:	
80-62-6 methyl methacrylate	F3, R2
· Pennsylvania Right-to-Know List:	
80-62-6 methyl methacrylate	
· Pennsylvania Special Hazardous Substance List:	
80-62-6 methyl methacrylate	E
· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
80-62-6 methyl methacrylate	E, NI
TLV (Threshold Limit Value established by ACGIH)	
80-62-6 methyl methacrylate	A4
· MAK (German Maximum Workplace Concentration)	`
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· National regulations:

- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- Department issuing SDS: Environment protection department.
- · Creation Date: 02/02/2017
- · Date of preparation / last revision 02/02/2017 / -• Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit

(Contd. on page 10)

Printing Date 02/02/2017

Revision Number 1

Revision Date 02/02/2017

Trade name: MP55300, MP55305, MP55315 Part B (Activator)

(Contd. of page 9)

USA

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3