



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155 Activator

Print date: 12.10.2015

Product code: 1155

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Parfix 1155 Activator

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Industrial and professional use.

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Parson Adhesives, Inc.
Place: Rochester MI 48309
Telephone: +1 248-299-5585
Internet: www.parsonadhesives.com
Responsible Department: sales@parsonadhesives.com

1.4. Emergency telephone number:

Chemtrec 1-800-262-8200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

Acetone

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use Water spray. Carbon dioxide. Extinguishing powder. Dry extinguishing powder. alcohol resistant foam. to extinguish.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 2 of 11

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | Quantity |
|---------|--|--------------|----------|------------|
| | EC No | Index No | REACH No | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | |
| 67-64-1 | acetone; propan-2-one; propanone | | | 50 - 100 % |
| | 200-662-2 | 606-001-00-8 | | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066 | | | |
| 99-97-8 | N,N-dimethyl-p-toluidine | | | 1 - < 5 % |
| | 202-805-4 | 612-056-00-9 | | |
| | Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H331 H311 H301 H373 ** H412 | | | |

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation causes narcotic effects/intoxication.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 3 of 11

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray. Carbon dioxide. Extinguishing powder. Dry extinguishing powder. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air.

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment. (See section 8.)

Remove all sources of ignition. Remove persons to safety. Ventilate affected area. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol.

6.2. Environmental precautions

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Wear personal protection equipment. (refer to chapter 8)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Heating causes rise in pressure with risk of bursting. Flammable vapours can accumulate in head space of closed systems.

Further information on handling

Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol.

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 4 of 11

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 20°C

Protect against: Light. heat. Cold. moisture. UV-radiation/sunlight.

7.3. Specific end use(s)

refer to section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|---------|-----------|------|-------------------|-----------|---------------|--------|
| 67-64-1 | Acetone | 500 | 1210 | | TWA (8 h) | WEL |
| | | 1500 | 3620 | | STEL (15 min) | WEL |

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. Protect skin by using skin protective cream.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Wear suitable gloves. DIN EN 374

Suitable material:

Butyl rubber. - Thickness of glove material: 0,5 mm

(Breakthrough time > 4 h)

penetration time (maximum wearing period): >= ~160 min.

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 5 of 11

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

exceeding exposure limit values

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|----------------|
| Physical state: | liquid |
| Colour: | colourless |
| Odour: | characteristic |

Test method

| | |
|-----------|----------------|
| pH-Value: | not determined |
|-----------|----------------|

Changes in the physical state

| | |
|--|-------------------|
| Melting point: | not determined |
| Initial boiling point and boiling range: | 56 °C |
| Sublimation point: | not determined |
| Softening point: | not determined |
| Pour point: | not determined |
| Flash point: | < -20 °C |
| Sustaining combustion: | No data available |

Flammability

| | |
|------|----------------|
| Gas: | not determined |
|------|----------------|

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

| | |
|-------------------------|-------------|
| Lower explosion limits: | 2,5 vol. % |
| Upper explosion limits: | 14,3 vol. % |
| Ignition temperature: | 370 °C |

Auto-ignition temperature

| | |
|------|----------------|
| Gas: | not determined |
|------|----------------|

Oxidizing properties

none

| | |
|--------------------------------|-----------------------------------|
| Vapour pressure: (at 20 °C) | 246 hPa |
| Vapour pressure: (at 50 °C) | 814 hPa |
| Density (at 20 °C): | 0,79 g/cm ³ |
| Water solubility: | not miscible - partially miscible |

Solubility in other solvents

miscible.

| | |
|------------------------------------|----------------|
| Partition coefficient: | not determined |
| Viscosity / dynamic: (at 20 °C) | not determined |



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 6 of 11

| | |
|--------------------------|---------------------------|
| Viscosity / kinematic: | No information available. |
| Flow time: (at 20 °C) | not determined |
| Vapour density: | No information available. |
| Solvent separation test: | not determined |
| Solvent content: | 50-100% |

9.2. Other information

Solid content: not determined

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Heating causes rise in pressure with risk of bursting. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

Ignition hazard. Keep away from heat. Protect against direct sunlight.

10.5. Incompatible materials

Hydrogen peroxide, bromine trifluoride, Difluordioxid, 2-methyl-1,3-butadiene, nitromethane, nitrosyl chloride (catalyst), Nitrosylperchlorat, alkali hydroxide, bromine, fluorine, sodium, strong reducing agents, nitric acid, chromic acid, chromium trioxide, chromyl chloride, ethanolamine, Potassium tert-butoxide. Oxidizing agents, strong.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 7 of 11

| CAS No | Chemical name | | | | |
|---------|----------------------------------|--------|-------------|---------|--------------|
| | Exposure routes | Method | Dose | Species | Source |
| 67-64-1 | acetone; propan-2-one; propanone | | | | |
| | oral | LD50 | 5800 mg/kg | Rat | ECHA Dossier |
| | dermal | LD50 | 7400 mg/kg | Rabbit | ECHA Dossier |
| | inhalative (4 h) vapour | LC50 | 50,1 mg/l | Rat | RTECS |
| 99-97-8 | N,N-dimethyl-p-toluidine | | | | |
| | oral | ATE | 100 mg/kg | | |
| | dermal | LD50 | >2000 mg/kg | Rat | ECHA Dossier |
| | inhalative (4 h) vapour | LC50 | 1,4 mg/l | Rat | GESTIS |
| | inhalative aerosol | ATE | 0,5 mg/l | | |

Irritation and corrosivity

Causes serious eye irritation.
Irritant effect on the eye: Irritant.
Irritant effect on the skin: Not an irritant.

Sensitising effects

Based on available data, the classification criteria are not met.
no danger of sensitization.
The statement is derived from the properties of the single components.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.
Acetone:
Subchronic oral toxicity (90d): NOAEL = 900 mg/m³ (Rat)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
Acetone:
No experimental indications of mutagenicity in-vitro exist. literature information: ECHA Dossier
Developmental toxicity/teratogenicity (Rat) NOAEL = 11000 ppm; literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

| CAS No | Chemical name | | | | | |
|---------|----------------------------------|--------|------------|-----------|----------------------|--------------|
| | Aquatic toxicity | Method | Dose | [h] [d] | Species | Source |
| 67-64-1 | acetone; propan-2-one; propanone | | | | | |
| | Acute fish toxicity | LC50 | 5540 mg/l | 96 h | Onchorhynchus mykiss | ECHA Dossier |
| | Acute crustacea toxicity | EC50 | 8800 mg/l | 48 h | Daphnia pulex | ECHA Dossier |
| 99-97-8 | N,N-dimethyl-p-toluidine | | | | | |
| | Acute fish toxicity | LC50 | 46-53 mg/l | 96 h | Pimephales promelas | GESTIS |

12.2. Persistence and degradability



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 8 of 11

| CAS No | Chemical name | Method | Value | d | Source |
|---------|----------------------------------|---|-------|----|--------------|
| 67-64-1 | acetone; propan-2-one; propanone | OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C | 90 | 28 | ECHA Dossier |
| | Product is biodegradable. | | | | |

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|----------------------------------|---------|
| 67-64-1 | acetone; propan-2-one; propanone | -0,24 |
| 99-97-8 | N,N-dimethyl-p-toluidine | 2,81 |

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Observe in addition any national regulations! Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Acetone)

14.3. Transport hazard class(es):

3

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 9 of 11

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Inland waterways transport (ADN)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Acetone)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2

Marine transport (IMDG)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Acetone)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Marine pollutant:

NO

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-E, S-E

Air transport (ICAO)**14.1. UN number:**

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Acetone)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 10 of 11



| | | |
|--|------|------|
| Special Provisions: | A3 | |
| Limited quantity Passenger: | 1 L | |
| Passenger LQ: | Y341 | |
| Excepted quantity: | E2 | |
| IATA-packing instructions - Passenger: | | 353 |
| IATA-max. quantity - Passenger: | | 5 L |
| IATA-packing instructions - Cargo: | | 364 |
| IATA-max. quantity - Cargo: | | 60 L |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

| | |
|---|-----------------------|
| 2010/75/EU (VOC): | 100 % (calculated.) |
| 2004/42/EC (VOC): | 790 g/l (calculated.) |
| Information according to 2012/18/EU (SEVESO III): | P5c FLAMMABLE LIQUIDS |

Additional information:

Additional information

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].
REACH 1907/2006 Appendix XVII: 3

National regulatory information

| | |
|--------------------------------|---|
| Employment restrictions: | Observe employment restrictions for young people. |
| Water contaminating class (D): | 2 - water contaminating |

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1.00; 12.10.2015 Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
CAS Chemical Abstracts Service
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parfix 1155

Print date: 12.10.2015

Product code: 1155

Page 11 of 11

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NTP: National Toxicology Program
N/A: not applicable
OSHA: Concerning the International Transport of Dangerous Goods by Rail)
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SARA: Superfund Amendments and Reauthorization Act
SVHC: substance of very high concern
TRGS Technische Regeln für Gefahrstoffe
TSCA: Toxic Substances Control Act
VOC: Volatile Organic Compounds
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)