

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

1 Identification

- **Product identifier**
- **Trade name:** ECOFLEX 9500 Black EF-71
- **Other means of identification**
- **Product Description:** Hybrid Elastomeric Sealant / Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Silco Inc.
7635 St. Clair Avenue
Mentor, OH 44060
Phone: 440-975-8886
Fax: 440-975-8887
www.silco-inc.com
- **Emergency telephone number:** 440-975-8886

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 1A	H350	May cause cancer.
Reproductive toxicity 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) 1	H370	Causes damage to organs.
Specific target organ toxicity (repeated exposure) 1	H372-H373	Causes damage to the kidneys and the liver through prolonged or repeated exposure. May cause damage to the lung, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin irritation 2	H315	Causes skin irritation.
Eye irritation 2A	H319	Causes serious eye irritation.
Sensitization - skin 1	H317	May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Calcium carbonate [Limestone]
Diisodecyl Phthalate

(Contd. on page 2)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: **ECOFLEX 9500 Black EF-71**

(Contd. of page 1)

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Quartz (SiO₂)

Trimethoxyvinylsilane

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

Causes damage to the kidneys and the liver through prolonged or repeated exposure. May cause damage to the lung, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

0 % of the mixture consists of component(s) of unknown toxicity.

Information pertaining to particular dangers for man and environment:

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



Health = 2

Fire = 1

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2

Fire = 1

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT:

25973-55-1 2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol

(Contd. on page 3)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 2)

· vPvB:	
25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol
· Classification according to (d)(1)(ii) of § 1910.1200	
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.	
· Hazards not otherwise classified	
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.	

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 471-34-1 RTECS: EV 9580000	Calcium Carbonate	≥15–≤60%
CAS: 1317-65-3	Calcium carbonate [Limestone] ⚠ Carcinogenicity 1A, H350; Specific target organ toxicity (repeated exposure) 2, H373; ⚠ Skin irritation 2, H315; Eye irritation 2A, H319	≥15–≤60%
CAS: 68515-49-1	Diisodecyl Phthalate ⚠ Reproductive toxicity 2, H361	≥15–≤40%
CAS: 57-11-4 RTECS: WI 2800000	Stearic Acid, pure	≥5–≤10%
CAS: 67-56-1 RTECS: PC 1400000	Methanol ⚠ Flammable liquids 2, H225; ⚠ Acute toxicity - oral 3, H301; Acute toxicity - dermal 3, H311; Acute toxicity - inhalation 3, H331; ⚠ Specific target organ toxicity (single exposure) 1, H370	≥1–<3%
CAS: 1760-24-3 RTECS: KV 7400000	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ Acute toxicity - inhalation 3, H331; ⚠ Eye damage 1, H318; ⚠ Skin irritation 2, H315; Sensitization - skin 1, H317; Specific target organ toxicity (single exposure) 3, H335	≥1–<3%
CAS: 2768-02-7	Trimethoxyvinylsilane ⚠ Flammable liquids 2, H225; ⚠ Sensitization - skin 1B, H317	1–5%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO ₂) ⚠ Carcinogenicity 1A, H350; Specific target organ toxicity (single exposure) 1, H370; Specific target organ toxicity (repeated exposure) 1, H372	1–5%
CAS: 25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol ⚠ Specific target organ toxicity (repeated exposure) 1, H372; ⚠ Acute toxicity - dermal 4, H312; Combustible Dust PBT; vPvB	1–5%

- **Additional information:**
The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: **ECOFLEX 9500 Black EF-71**

(Contd. of page 3)

· **After inhalation:**

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get immediate medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

If eye irritation occurs, consult a doctor.

If easy to do so, remove contact lenses if worn.

· **After swallowing:**

Do not induce vomiting.

If conscious, give no more than two glasses of water.

Seek medical treatment.

If swallowed and symptoms occur, consult a doctor.

· **Most important symptoms and effects, both acute and delayed**

May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.

· **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

Hazardous decomposition products include: carbon dioxide, carbon monoxide, formaldehyde, silicon dioxide, nitrogen oxides and incompletely burnt hydrocarbons.

· **Advice for firefighters**

· **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

· **Additional information** Cool fire exposed containers with water.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothing.

Do not breathe vapor.

Product is slippery when spilled.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers / surface or ground water.

· **Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 4)

· Protective Action Criteria for Chemicals

Protective Action Criteria (PACs) are essential components for planning and response to uncontrolled releases of hazardous chemicals.

· PAC-1:

PAC 1: Mild, transient health effects.

471-34-1	Calcium Carbonate	45 mg/m ³
57-11-4	Stearic Acid, pure	14 mg/m ³
67-56-1	Methanol	530 ppm
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	23 mg/m ³
2768-02-7	Trimethoxyvinylsilane	9.5 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

· PAC-2:

PAC 2: Irreversible or other serious health effects that could impair the ability to take protective action.

471-34-1	Calcium Carbonate	210 mg/m ³
57-11-4	Stearic Acid, pure	150 mg/m ³
67-56-1	Methanol	2,100 ppm
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	250 mg/m ³
2768-02-7	Trimethoxyvinylsilane	100 ppm
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³

· PAC-3:

PAC 3: Life-threatening health effects.

471-34-1	Calcium Carbonate	1,300 mg/m ³
57-11-4	Stearic Acid, pure	910 mg/m ³
67-56-1	Methanol	7200* ppm
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	1,500 mg/m ³
2768-02-7	Trimethoxyvinylsilane	120 ppm
14808-60-7	Quartz (SiO ₂)	50 mg/m ³

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Avoid contact with skin, eyes and clothing.

Avoid breathing fume/gas/mist/vapors/spray.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool, dry place.

Store in a well-ventilated place.

Store in the original container.

(Contd. on page 6)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 5)

Protect from moisture.

- **Information about storage in one common storage facility:** See Section 10 (Incompatible materials)
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

471-34-1 Calcium Carbonate	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn
1317-65-3 Calcium carbonate [Limestone]	
PEL	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³
TWA	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³
68515-49-1 Diisodecyl Phthalate	
PEL	Short-term value: 5 mg/m ³
57-11-4 Stearic Acid, pure	
TLV	Long-term value: 10* 3** mg/m ³ *inhalable, **respirable particulate matter, *A4
67-56-1 Methanol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI
14808-60-7 Quartz (SiO ₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2

(Contd. on page 7)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 6)

Ingredients with biological limit values:	
67-56-1 Methanol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls**

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



NIOSH/OSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Limitation and supervision of exposure into the environment**

Keep away from drains, surface and ground waters.

Avoid release into the environment.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

(Contd. on page 8)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 7)

· Color:	Black
· Odor:	Slight
· Odor threshold:	Not determined.
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	≥250 °C (≥482 °F)
· Flammability:	Not applicable.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>200 °C (>392 °F)
· Auto igniting:	≥395 °C (≥743 °F)
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic:	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure at 174 °C (345.2 °F):	1.5 hPa (1.1 mm Hg)
· Vapor pressure:	
· Density at 20 °C (68 °F):	1.66 g/cm ³ (13.8527 lbs/gal)
· Relative density	Not determined.
· Vapor density	

ECOFLEX 9599 Natural	>1 Aire=1
----------------------	-----------

· Particle characteristics	Not applicable.
· Other information	
· Appearance:	
· Form:	Paste
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Solvent content:	
· Organic solvents:	≤2.5 %
· VOC content:	≤2.50 %
	≤41.5 g/l / ≤0.35 lb/gal
· Change in condition	
· Oxidizing properties	None
· Evaporation rate	

ECOFLEX 9599 Natural	<1
----------------------	----

10 Stability and reactivity

- **Reactivity**
The product is stable under normal conditions.
No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Thermal decomposition will result in carbon monoxide, carbon dioxide and or low molecular weight hydrocarbons.

(Contd. on page 9)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 8)

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid**

Avoid sparks, flame and excessive heat.

Incompatible Materials

· **Incompatible materials:**

Strong acids

Strong oxidizing agents.

· **Hazardous decomposition products:**

Upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	>44,000 mg/kg
Inhalative	LC50/4 h	≥39.8–53.8 mg/l

471-34-1 Calcium Carbonate

Oral	LD50	6,450 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>3 mg/l (rat)
	LC50/96 hours	>56,000 Mg/l (fish)

57-11-4 Stearic Acid, pure

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

67-56-1 Methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral	LD50	2,413 mg/kg (rat)
Dermal	LD50	>2,009 mg/kg (rat)
		16 mg/kg (rabbit)
Inhalative	LC50/96 hours	1.49–2.44 Mg/l (rat)
		597 Mg/l (zebrafish)
	LC50	>100 mg/l (fish)

2768-02-7 Trimethoxyvinylsilane

Oral	LD50	7,120–7,236 mg/kg (rat)
Dermal	LD50	3,600–4,000 mg/kg (rabbit)

14808-60-7 Quartz (SiO2)

Oral	LD50	>22,500 mg/kg (rat)
Inhalative	LC50/96 hours	1,033 Mg/l (trout)

(Contd. on page 10)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 9)

25973-55-1 2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol		
Oral	LD50	>7,750 mg/kg (rat)
Dermal	LD50	>1,100 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:**

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Interactive effects** No interactive effects between components are known.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

According to the IARC (International Agency for Research on Cancer), CAS number 14808-60-7, which corresponds to Quartz (SiO₂), is classified as a Group 1 carcinogen, meaning there is sufficient evidence that it can cause cancer in humans when inhaled as respirable crystalline silica dust; there is no "exception" to this classification, meaning quartz is considered carcinogenic under all exposure conditions relevant to occupational exposure.

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

· **NTP (National Toxicology Program)**

K = Known to be a human carcinogen

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Alternative sources for toxicological information**

No non-standard sources for toxicological information where used.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

471-34-1 Calcium Carbonate	
EC50	>1,000 mg/kg (daphnia)
1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine	
EC50	81 mg/kg (daphnia)
	90 mg/kg (daphnia)
	8.8 mg/kg (Green algae)
2768-02-7 Trimethoxyvinylsilane	
EC50	168.7 mg/kg (daphnia)

(Contd. on page 11)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 10)

14808-60-7 Quartz (SiO₂)	
EC50	218 mg/kg (Green algae)
25973-55-1 2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol	
EC50	>100 mg/kg (daphnia)

· **Persistence and degradability** No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Results of PBT and vPvB assessment**

· **PBT:**

25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol
------------	---

· **vPvB:**

25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol
------------	---

· **Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

Non-Regulated Material

· **UN proper shipping name**

· **DOT, IMDG, IATA**

Non-Regulated Material

· **Transport hazard class(es)**

· **DOT, ADN, IMDG, IATA**

· **Class**

Non-Regulated Material

· **Packing group**

· **DOT, IMDG, IATA**

Non-Regulated Material

· **Environmental hazards:**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Special precautions for user**

Not applicable.

· **UN "Model Regulation":**

Non-Regulated Material

(Contd. on page 12)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 11)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 Methanol

· TSCA (Toxic Substances Control Act):

471-34-1	Calcium Carbonate	ACTIVE
1317-65-3	Calcium carbonate [Limestone]	ACTIVE
68515-49-1	Diisodecyl Phthalate	ACTIVE
57-11-4	Stearic Acid, pure	ACTIVE
67-56-1	Methanol	ACTIVE
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	ACTIVE
2768-02-7	Trimethoxyvinylsilane	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
25973-55-1	2-(2H-benzotriazol-2-yl)-4,6-di-tert-pentylphenol	ACTIVE

· Hazardous Air Pollutants

67-56-1 Methanol

· Proposition 65

· Chemicals known to cause cancer:



WARNING: This product can expose you to chemicals including [one or more listed chemical] which is [are] known to the State of California to cause cancer [or birth defects or other reproductive harm]. For more information, go to www.P65Warnings.ca.gov.

14808-60-7 Quartz (SiO₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

68515-49-1 Diisodecyl Phthalate

67-56-1 Methanol

· New Jersey Right-to-Know List:

1317-65-3 Calcium carbonate [Limestone]

67-56-1 Methanol

14808-60-7 Quartz (SiO₂)

· New Jersey Special Hazardous Substance List:

67-56-1	Methanol	TE, F3
14808-60-7	Quartz (SiO ₂)	CA

(Contd. on page 13)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 12)

· Pennsylvania Right-to-Know List:		
1317-65-3	Calcium carbonate [Limestone]	
14808-60-7	Quartz (SiO ₂)	
· Pennsylvania Special Hazardous Substance List:		
None of the ingredients is listed.		
· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value)		
14808-60-7	Quartz (SiO ₂)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Calcium carbonate [Limestone]

Diisodecyl Phthalate

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Quartz (SiO₂)

Trimethoxyvinylsilane

· **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

Causes damage to the kidneys and the liver through prolonged or repeated exposure. May cause damage to the lung, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

(Contd. on page 14)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07.

Date of issue: 03/04/2025

Reviewed on 03/04/2025

Trade name: ECOFLEX 9500 Black EF-71

(Contd. of page 13)

Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Specific treatment (see on this label).
If eye irritation persists: Get medical advice/attention.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **SDS created by:** Access GHS, LLC - 888-363-4870 - Team@access-ghs-sds.com

· **Date of previous version** 02/08/2019

· **Version number of previous version:** 1

· **Date of preparation** 03/04/2025

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable liquids 2: Flammable liquids – Category 2

Acute toxicity - oral 3: Acute toxicity – Category 3

Acute toxicity - dermal 4: Acute toxicity – Category 4

Skin irritation 2: Skin corrosion/irritation – Category 2

Eye damage 1: Serious eye damage/eye irritation – Category 1

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - skin 1: Skin sensitisation – Category 1

Sensitization - skin 1B: Skin sensitisation – Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

Reproductive toxicity 2: Reproductive toxicity – Category 2

Specific target organ toxicity (single exposure) 1: Specific target organ toxicity (single exposure) – Category 1

Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3

Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1

Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2