

ADHESION PRODUCTS

22290 Challenger Drive

Elkhart, IN 46514

(O) 574-970-8425 / (F) 574-970-8428

www.titansc.com

**TECHNICAL DATA SHEET****AP-002-XS-5397****PRODUCT DESCRIPTION:**

Adhesion Products AP-002-XS-5397 is a quick setting, HAP's free low pressure sprayable adhesive that has been designed to produce a strong permanent bond when used with a variety of insulation materials.

SURFACE PREPARATION:

AP-002-XS-5397 should only be applied to clean, dry surfaces. Best bonds are obtained if substrates are maintained at temperatures above 40 degrees F. Drying time and coverage per gallon will vary according to the rate of adhesive application and local atmospheric conditions. Suitable equipment for spray application is listed below, however, other equivalent spray equipment is available.

Manufacturer	Model	Air Cap	Fluid Tap
Binks	2001SS	665D	63A
Binks	18	66PJ	66
De Vilbiss	MBC	770	FX
De Vilbiss	JGA	770	FX

PACKAGING:

54 gl. Drum

TECHNICAL SPECIFICATIONS:

Color:	Amber
Viscosity:	450 cPs
Base:	Synthetic Rubber
Solvent:	Heptane/acetone
Solids:	40%
Wt./Gal:	6.8 pounds

Limited Warranty:

Adhesion Products warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, ADHESION PRODUCTS MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and ADHESION PRODUCTS shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.