



## TECHNICAL DATA SHEET AT-BBT Bottom Board Barrier Tapes

### PRODUCT DESCRIPTION:

AT-BBT Bottom Board Barrier Tapes are extremely aggressive, self-adhering flashing membrane designed to protect against moisture penetration.

### PRODUCT CHARACTERISTICS:

AT-BBT Tapes utilizes a block co-polymer base adhesive to promote superior adhesion to OSB, plywood, aluminum, vinyl, and weather resistive barriers in extreme conditions. AT-BBT Tapes exceed all current AAMA 711 standards. Available with black or white backing.

- Bottom Board Wrap in RV's
- Window and Door Flashing
- Roof/Wall Transition
- Building Envelope Application

### TECHNICAL SPECS:

Raw Material Base	Block Co-Polymer	UV Exposure	Resistant Up To 6 Mos.	
Application Temperature	-40°f – 150°F	Life Expectancy	>10 Years	
Service Temperature	-40°f – 225°f	Mold Growth	Shelf Life	18 Months
ASTM G-21	No Growth	Physical State	Solid	
Nail Sealability (AAMA 711-07)	Pass	Odor	Odorless	
Nail Sealability (ASTM D-1970)	Pass	Staining	None	
90° Peel Plywood (AAMA 711-07)	5 PSI	USGBC	Eligible For Leed Compliance Credits	
90° Peel OSB (AAMA 711-07)	3.8 PSI	Adhesive Thickness	7 Mil	
90° Peel Facer (AAMA 711-07)	4.6 PSI	Solids By Weight	100%	

### APPLICATION INFORMATION:

Ensure all involved surfaces are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. Anaconda AT-BBT Bottom Board Barrier Tapes feature a strong, flexible backing, allowing it to form to fasteners and corners.

### PACKAGING & HANDLING:

Do not open until ready for use in order to maximize shelf life. Store at 60° – 80°F. This product is available in standard roll widths of 4" and 6", with custom sizes up to 55" wide. Standard roll length is 75 feet. Available with a black or white outer surface.

### Limited Warranty:

Titan warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, TITAN MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and TITAN shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.