

Anaconda Tape
22290 Challenger Drive
Elkhart, IN 46514
(574) 970-8425 / (574) 970-8428 (f)
www.titansc.com



TECHNICAL DATA SHEET
Anaconda Butyl Tapes
AT-BT(X)-ECO Series

PRODUCT DESCRIPTION:

Anaconda Butyl Tape ECO Series Butyl Tapes AT-BTG-ECO (gray) and AT-BTB-ECO (black)) are versatile, high quality butyl tapes formulated to provide high levels of adhesion, elongation, and pliability. Anaconda AT-BT(X)-ECO Series Butyl Tapes are a non-drying compound that features excellent resistance to weather, water, and air intrusion, while trimming easily.

PRODUCT CHARACTERISTICS:

Anaconda Butyl Tapes are well-suited for use in the following industries and applications;

- Roof Seam Sealing
- RV Manufacturing
- Construction
- Trailer Manufacturing
- Window and Door sealing
- Manufactured Housing

TECHNICAL SPECS:

Standard Colors	Gray & Black, other colors upon request
Specific Gravity (ASTM 792)	15.4 lb. / gal.
AAMA	807.1-85
Low Temp Flex (ASTM 765)	No Loss of Adhesion
Oil Migration/Plasticizer Bleed-Out (ASTM 772)	Slight Wetting of top sheet / No bleed
Softness mm Penetration (ASTM C782)	9.7
Tensile Adhesion Strength, lb. force (ASTM C907)	34.0 MOF: Cohesion
Yield Strength, lb. force (ASTM C908)	8.0

SURFACE PREPARATION:

All surfaces to be sealed should be free of dust, dirt, oil, moisture, grease, etc. before applying tape.

APPLICATION INFORMATION:

Anaconda AT-BT(X)-ECO Series Butyl Tapes are extruded onto removable silicone release paper backing to facilitate handling. It is recommended that the material be pressed onto one surface, stripped of its paper backing, and then brought into intimate contact with the second surface to assure a watertight seal. When using to seal applications involving fasteners, position on the entry side to prevent the penetration of contaminants through fastener holes. When lapping tape, allow at least ¼" (6.4 mm) overlap.

PACKAGING & HANDLING:

Anaconda AT-BT(X)-ECO Series Butyl Tapes are available in a variety of different widths, thicknesses, and roll dimensions. No special handling is required for this product, though storage in a cool, dry area is recommended for maximum shelf life and effectiveness. Tools and equipment used while applying Anaconda Butyl Tapes can be cleaned using mineral spirits, if necessary.

Limited Warranty:

Titan warrants product to be of good quality and will replace or, at our election, refund the purchase price of any products proved to be defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, TITAN MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and TITAN shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.