



Anaconda PE 4310-R Foam Tape Series Technical Data Sheet

Product Description:

AT-PE-4310-R Foam Tape series is constructed of a polyethylene foam coated on both sides with our strongest bonding solvent rubber pressure sensitive adhesive. This product offers high tack, high peel, and excellent shear strength. The AT-PE-4310-R Foam Tape series is used in the most demanding applications.

Features / Benefits:	Applications:	Construction:
<ul style="list-style-type: none"> - High Tack & Peel - Excellent Shear - Great for Die Cutting - Excellent Adhesion 	<ul style="list-style-type: none"> - Indoor Applications - POP Displays - General Purpose Mounting 	<p>Type: Double Coated PE Foam Tape</p> <p>Carrier: PE Foam</p> <p>Adhesive Type: Solvent Rubber</p> <p>Liner: SCK Liner</p>

Physical Characteristics:

Product Number	Color	Peel Adhesion	Loop Tack	Shear Adhesion	Density	Operating Temperature (°F)
AT-PE-4310-R-031	White, Black	125 Oz / Inch	38 Oz / In	24 + Hours	6 # / Cu. Ft	+10 to +185
AT-PE-4310-R-063	White, Black	125 Oz / Inch	38 Oz / In	24 + Hours	4 # / Cu. Ft	+10 to +185
AT-PE-4310-R-125	White, Black	125 Oz / Inch	38 Oz / In	24 + Hours	3 # / Cu. Ft	+10 to +185

Storage Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. Anaconda Tape can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70° (21°C) with 50% relative humidity.

22290 Challenger Drive
Elkhart, IN 46514
(574) 970-8425 (O)
(574) 970-8426 (F)
www.titansc.com