



STICKY STUFF

General Purpose Adhesive

Non-Chlorinated

Our Multi-Purpose Adhesive was designed for a permanent bond.

Advantages of Max-Tite Adhesive Systems:

- Water Resistant
- Fast flash time 1-2 minutes
- Economical cost with labor and material savings
- No Ozone Depleting Chemicals
- High Strength
- High Temperature
- VOC Compliant
- Will not Freeze
- Dries Clear in 15 minutes
- Solids 18-20%

Applications:

Works on the following surfaces:

Foam, Fabric, Duct Liner, Metals, Wood, Fiberglass, Carpet Backings, and many others

“Always test compatibility of substrates”

Spraying Techniques:

Clean surface making sure to leave behind no dirt, grease, etc. Hold spray perpendicular to surface, six (6) to ten (10) inches from area to be sprayed. Using a full arm movement vs a wrist movement apply adhesive in an even coat. This arm movement will maintain a more even application of the adhesive. Over lapping the edges of the adhesive will insure 100% coverage. Take care not to apply excessive adhesive, or allow bubbling or build up on substrate. Porous surfaces and edge areas may require a double coating to insure a permanent bond. It is always best to use opposite direction technique (spray one substrate north and south and the other east and west) this will allow cross bonding of the adhesives and a stronger bond.



Max-Tite Adhesive Systems warrants its product to be free from manufacturing defects for a period of one year from date of purchase. The company shall not be liable for any consequential or other damage or remedy, its sole obligation and your exclusive remedy are limited to product replacement or refund of the purchase price. User shall determine suitability of the product for their intended use and shall assume all risk and liability associated therewith

Max-Tite Adhesive Systems, Inc. Decatur, AL 866-748-5854 Fax 678-528-7842