

HI-COMPRESSION TAPES
ADHESIVES • SEALANTS
SPECIAL INDUSTRIAL PAINTS
CUSTOM MECHANICAL EQUIPMENT

SALES • SERVICE ENGINEERING
CONSULTING ENGINEERING
NEW PRODUCT DESIGN



TECHNICAL DATA

MANUS-BOND 76-AM


HIGH PERFORMANCE SELF-LEVELING ELASTOMERIC ADHESIVE/SEALANT

1. PRODUCT DESCRIPTION:

Manus-Bond 76-AM exhibits excellent adhesion to many substrates including aluminum, brass, steel, glass, mortar, granite, marble, wood and many plastics. Cures fast, even at low temperatures. 76-AM is highly weather resistant and can be painted with most paints. Contains no solvents or isocyanates and is non-yellowing. USDA Accepted. Complies to AAMA 803.3-92 Type II.

2. TECHNICAL DATA:

Tack Free Time	Less than an hour @ 77°F/50% RH
Skin Time	Less than 30 minutes @ 77°F/50% RH
Sag	Self-leveling
Tensile Strength (ASTM D412)	175 psi
Lap Shear (ASTM D1002)	210 psi
Adhesion-n-Peel	36 pli
Elongation	150%
High Temperature Resistance	Up to 400°F for short periods
Low Temperature Flexibility	Properties retained to -75°F
Hardness - Shore A	50
UV Ratings	After 2000 hours UV-A no change in appearance Or physical properties (ASTM G26)
Corrosive Properties	Non-corrosive
Staining	Non-staining



3. COLORS:

White, aluminum gray, black. Other colors available upon request.

4. PACKAGING:

10.3 oz. cartridges, 10.3 oz. & 20 oz. sausage packs, 1, 3, 5, & 50 gallon containers.

5. SURFACE PREPARATION:

Apply to clean, dry surfaces free of contaminants that can adversely effect adhesion. Remove all old sealant before applying 76-AM.

6. PAINTING:

Cured 76-AM may be painted with most industrial and commercial paints. Testing prior to painting is recommended.

7. STORAGE LIFE:

Nine months. For maximum shelf life, store unopened product at or below 80° F.

8. PRECAUTIONS:

Use with adequate ventilation. Inhalation of vapor during application and cure may cause slight eye or throat irritation. In case of contact with eyes, lips, or mouth, flush thoroughly with water. If irritation persists, consult a physician. Avoid repeated, prolonged contact with skin. Do not take internally. See MSDS for additional information. **KEEP OUT OF REACH OF CHILDREN.**

9. TECHNICAL SERVICE:

For further information and assistance concerning this product, please call our Technical Service Department at 952-442-3323 or Fax 952-442-3327.

10. LIMITED WARRANTY:

Any goods proved defective will be replaced or the purchase price refunded. The limited warranty described herein is in lieu of any other warranty, expressed or implied, including any implied warranty of merchantability or fitness for a particular use. The user shall determine suitability of the product for its intended use. Liability for any incidental or consequential damage or loss is excluded. The user assumes all risks of the product's use, handling and storage.

Distributed by



MANUS PRODUCTS, INC.

866 INDUSTRIAL BLVD. WEST • WACONIA, MINNESOTA 55387
PHONE (952) 442-3323 • FAX (952) 442-3327
www.manus.net • info@manus.net

NAPLES, FL • CHASKA, MN