

## Specification Data Sheet

Product: **PE- 1302**

General Description: A Premium hot melt formulated for general case and carton sealing and tray forming applications. It is recommended for bonding a wide variety of paperboard substrates. Final bonds stay strong in extreme heat & cold temperatures. The PE-1302 displays consistent trouble-free performance, elimination of char, low-odor, and increased mileage over traditional EVA products.

### Typical Properties:

Color: White

Application Temperature: 325-375°F

Viscosity at 350° F: 1000 cps.

Tack: Aggressive

Open Time: Short

Softening point: 230°F

Product Form: Pellets

Packaging and Shipped: 40 lb. corrugated boxes palletized and shrink wrapped at 36 boxes per pallet for a total of 1440 pounds

Specific Gravity: 0.96

Components contained in this product conform to USDA and FDA regulations for use in food packaging, as stated in the Federal Food and Drug & Cosmetic Act, title 21 under section 175-105. This guarantee is also intended to comply with USDA's "Policy Governing Inspection of Packaging Materials." NOTE: The data presented is based upon tests believed to be reliable; however, Tailored Chemical Products, Inc., does not guarantee their accuracy or completeness. Tailored Chemical Products, Inc., assumes no responsibility for results obtained or for incidental or consequential damages arising from the use of this data.