

DATA SHEET PS-1216

DESCRIPTION

PS-1216 is a specially formulated hot melt pressure sensitive adhesive designed for high shear resistance at elevated temperature. Its intended use is for removable sanding pads. It meets composition requirements of Indirect Food Additives Regulation 21 CFR 175.105 "Adhesives."

TYPICAL PHYSICAL PROPERTIES

35,000 cps @ 300 degrees F
12,000 cps @ 325 degrees F
5,000 cps @ 350 degrees F

Ring and ball softening point 235 degrees F

Running Temperature 330 F to 360 F

FORM

350 pound drums

Lb./Gal

Approx. 8.2

THE INFORMATION HEREIN IS TO ASSIST CUSTOMERS IN DETERMINING WHETHER OUR PRODUCTS ARE SUITABLE FOR THEIR APPLICATION. WE REQUEST THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. NOTHING HEREIN SHALL CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS, NOR IS PROTECTION FROM ANY LAW OR PATENT INFERRED. ALL PATENT RIGHTS ARE RESERVED. THE EXCLUSIVE REMEDY FOR ALL PROVEN CLAIMS IS REPLACEMENT OF OUR MATERIALS.