TECHNICAL DATA SHEET

# 150C PVC Clean Room Tape

## DESCRIPTION

PVC Clean Room Tape is designed for use in controlled environments like cleanrooms and sensitive environments where contamination control and compliance with strict standards is critical. Constructed from soft WHITE PVC film and rubber adhesive, 150C is manufactured and packaged in ISO-compliant cleanroom facilities to minimize particle shedding and chemical outgassing and wound on PLASTIC cores. It offers strong adhesion to various surfaces including floors, glass, metal and plastic.

## FEATURES

- Soft plasticized and stabilized PVC with rubber adhesive designed to remove cleanly from many surfaces
- Conformable to most surfaces
- Matte finish and abrasion resistant- will not fade
- Resists oil, grease and many solvents
- White color on plastic cores
- Meets ISO 5 (Class 100) standards and sold to commercial items description A-A-1689 Type II (supersedes PPP-T-66E)

## APPLICATIONS

- Industrial identification and color coding
- Marking hazardous areas, creating pathways and securing protective barriers in cleanroom environments
- Ideal for industries including pharmaceuticals, biotechnology, microelectronics, aerospace and hospitals
- Protects surfaces like stainless steel, glass and plastics from scuffs or damage

## PHYSICAL PROPERTIES

| | |
|---|---|
| Color | White |
| Total Thickness (ASTM D-1000) | 6 mils |
| Adhesion to Steel (PSTC-101) | 18 oz/in |
| Tensile Strength | 14 lbs/in |
| Elongation | 150% |
| Operating Temperature Range | 40°F-140°F |

*The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.*

620TL